



# CONTEG DATA SHEET

version: 01-09-2010

PREMIUM RACK SERIES

## ROR / ROP SERIES 19" FREE STANDING RACKS

### CONTEG, spol. s r.o.

Headquarters Czech Republic:  
Na Vítězné pláni 1719/4  
140 00 Prague 4

Tel.: +420 261 219 182  
Fax: +420 261 219 192  
[conteg@conteg.com](mailto:conteg@conteg.com)  
[www.conteg.com](http://www.conteg.com)

### Local Offices:

Austria:	+43 699 1819 7071
Benelux:	+32 477 957 126
Eastern Europe:	+49 172 848 4346
France:	+33 686 074 386
Germany:	+49 170 523 4958
Russia:	+7 495 506 1328



## ROR SERIES 19" FREE STANDING RACKS

The ROR rack is based on the ROF concept and equipped with a swing frame. Owing to the swing frame, front access and maintenance of the installed equipment is significantly improved. Therefore, the rack is suitable for all PC rooms where access to the rack is limited.



### DESCRIPTION

#### Sizes

- Height: 27, 42, 45U
- Width: 800mm
- Depth: 600 or 800mm

#### Construction

- Welded frame construction
- 1.5 & 2.0mm sheet steel

#### Asymmetric frame placing

- Max. useful depth 450mm
- Frame opening angle 90°
- Cover on side of swinging part perforated for easy cable management
- Useful height of swing frame 3U is less than rack height
- Swing frame conductible connected with rack

#### Load rating of swing frame

- Max. 100kg; for load higher than 50kg is front stabilizer required (on request)

### COLOR SAMPLER:

RAL 9005

RAL 7035

#### IP rating

- Standard IP30

#### Colors

- Standard RAL 7035 and 9005
- Optionally other colors

#### Front door

- Same as ROF series

#### Side panels

- Same as ROF series

#### Feet

- Adjustable feet as standard; castors, lockable castors, plinth, or plinth with filter optionally

#### Adaptation

- Possibility to install one pair of sliding 19" vertical extrusions in the rear of rack

Code	H in Units		Dimensions in mm			Dimensions including packing in mm			Gross weight in kg
	(total/useful)	H*	W	D	Useful Depth	H	W	D	
ROR-27-80/60	27/24	1321	800	600	450	1500	840	640	89
ROR-42-80/60	42/39	1988	800	600	450	2160	840	640	120
ROR-45-80/60	45/42	2121	800	600	450	2290	840	640	128
ROR-27-80/80	27/24	1321	800	800	450	1500	840	840	110
ROR-42-80/80	42/39	1988	800	800	450	2160	840	840	140
ROR-45-80/80	45/42	2121	800	800	450	2290	840	840	144

\* Height in mm without feet; for feet add 16-45mm

## ROP SERIES 19" FREE STANDING RACKS

The ROP racks have emerged from the ROF concept too. They were redesigned for secure housing of a Personal Computer, however, it is also possible to install standard 19" equipment. Owing to the special design of the rack, a PC is positioned safely and the user is not limited in any way.



### DESCRIPTION

#### Sizes

- Height: 36U
- Width: 650
- Depth: 600 or 800mm

#### Construction

- Welded frame construction
- 1.5 & 2.0mm sheet steel

#### IP rating

- Standard IP30
- Optionally IP54 (recommended when placing in industrial deployment is planned)

#### Load rating

- Frame - 400kg
- Bottom section - 300kg
- Top section - 100kg
- Pull-out shelf - 10kg

#### Colors

- Standard RAL 7035
- Optionally other colors

#### Front door

- Tinted security glass door with swivel handle

### COLOR SAMPLER:

RAL 7035

lock – top part (12U)

- Sheet steel door with swivel handle lock – bottom part (22U)
- Door opening angle 180°
- Middle part (pull-out shelf) is locable (2U)

#### Rear panel

- Removable with lock
- Sheet steel or perforated sheet steel

#### Side panels

- Removable with lock
- Sheet steel or perforated sheet steel

#### Cable entries

- In the top and bottom plate
- Covered by removable blank panels

#### Ventilation unit openings

- In the top and bottom plate
- All ventilation unit openings covered by removable blank panels

#### Feet

- Adjustable feet as standard; castors, lockable castors, plinth, or plinth with filter optionally

Code	H in Units		Dimensions in mm			Dimensions including packing in mm			Gross weight in kg
	(total/useful)	H*	W	D	Useful depth	H	W	D	
ROP-36-65/60	36	1721	650	600	590	1850	690	660	105
ROP-36-65/80	36	1721	650	800	790	1850	690	890	119

\* Height in mm without feet; for feet add 16-45mm

ROR / ROP series 19" free standing racks