DATASHEET
Smart
Terminal
Display

CONTEG

RMS-CPS-DISPLAY

21,5" touch monitor with built-in computer (Linux OS). It can be used for remote access to CONTEG Pro Server (CPS) and other applications, or as a web kiosk. The monitor can be used to monitor current information in the data hall, e.g. for individual aisles or the entire data center.

The monitor can be mounted on a VESA bracket/stand to connect to the CPS application in the monitoring room. Cable outlets are provided on 4 sides (top, bottom, left and right) for easy cabling. There are also 4 holes in the corners of the monitor for wall or rack side panel mounting.

Passive cooling makes this touchscreen monitor with built-in single board computer very quiet. On the bottom side there are buttons to adjust the monitor.

Using the VNC application, remote access to the touchscreen displays of CONTEG cooling units is possible.

Technical Information:

Monitor:

Diagonal:	21,5"
Resolution:	Full HD (1920 × 1080 pixels)
Surface:	Anti-reflective with 3H hardened layer

PC:

Specifications:	4GB RAM, quad-core Cortex-A55 processor (2.016 GHz) with Amlogic S905X3 SoC and next generation GPU: Mali-G31
eMMC memory:	min. 16 GB
OS:	LINUX (Ubuntu Mate)
LAN port:	10/100/1000 Mbps
Mounting:	on rack, wall or VESA bracket (200x200)
Dimensions:	length 557 x width 38 x height 458 mm
Power:	175-264V AC, 50/60Hz, 1-0.65A
Int. fuse:	1.5 - 2 A (for 230V AC, 5x20mm glass housing)
Interní zdroj:	12V DC 8,3A (100W

CONTEG, spol. s r.o.
Stetkova 1638/18
140 00 Prague 4
Czech Republic

Tel.: +420 565 300 358
info@conteg.com
www.conteg.com